

WWW.ITRONBIRDCAM.COM

- Simple, Cable-free Installation
- Clear, Smooth Images with Intelligent Transmission
- Online Firmware Upgrades with Synchronous Updates
- Two-way Voice Talk with Echo Elimination and Noise Reduction
- Android and iOS Smart Terminal Remote Real-time Monitoring
- 3MP (Super HD) Image Quality
- Infrared Light with 7m Night Vision, 24-hour Monitoring, IR-cut Switching For Day/Night
- Built-in Rechargeable Lithium Battery, 6 Months Normal Use, 12 Months Standby
- Supports 2.4G Wi-Fi (IEEE 802.11 b/g/n)
- Smart Storage, Supports Micro SD Card (Up To 128gb), Cloud Storage
- QR Code Support for Camera Connection
- Humanoid, Vehicle, Pet, and Package Detection (Value-added Services)
- IP65 Dustproof and Waterproof, Easy Installation with 1/4 Universal Screw Bracket

SPECIFICATIONS		
Processor	SOC	ARM
Sensor	Sensor	1/2.9" color CMOS sensor
	Lens	M12, f:3.3mm, F2.0, 2MP
	View Angle	Horizontal (H) 150° / Vertical (V) 85° / Diagonal (D) 180°
	Low Illumination	0.01Lux
Audio	Input/output	Two-way Voice Talk (Built-in Microphone and Speaker)
	Audio Compression	AAC
Video	Video Compression	H.264 / H.265
	Light Frequency	50Hz, 60Hz
	Frame Rate	15 fps
	Maximum Image	3MP (Super HD)
	Night Vision	8 Low Power Infrared Lamps or 2 Medium Power Infrared
	Tright Vision	Lamps (850nm Wavelength) - Optional White Lightsource
Network	Wireless Network	2.4G WiFi (IEEE802.11b/g/n), Buily-in Antenna
	Agreements	TCP/IP, UDP/IP, DHCP, RTMP, MUTP
	IP Address	Dynamic IP address
Alarm	Smart Function	Support Humanoid Detection, Vehicle Detection,
	Smartranetion	Pet Capture, And Package Detection
	Alarm Notification	Mobile APP Alarm Push, Alarm Sound Warning and
Aldriii	Aldiff Notification	Equipment White Light Flashing (Optional)
Wake up	Make He Made	PIR Human Body Induction Wake Up,
	Wake Up Mode	· ·
Record	Record Method	Remote Active Wake Up
		Alarm Triggered, Manual Recording
Indication	Storage	Cloud/ Micro SD/ Mobile storage
	LED Indication	RGB Three Colors Light, Indicating Power Supply /
B #	0 133	Network Signal / Function Status
Battery	Capability	5200mAh / 6700mAh (Optional)
	Detachability	Non-detachable
	Usage Time	6 months (under the condition of recording 20, 10s videos
	0. " =	per day)
	Standby Time	12 months
	Charging Voltage	DV 5V+-% / 1.5A
	Charging Time	10 Hours
Consumption	Protection Mode	Over Current/ Over Discharge/Overcharge / Short Circuit /
		High & Low Temperature Charging Protection
	Standby Power Consumption	1.68mW (4V 0.42mA)
	Daytime Power Consumption	1W (3.8V 264mA)
	Night Power Consumption	2.17W (3.8V 571mA)
Port	Power	1 Micro Usb Port, Compatible With Type C Interface
	SD Card	1 Microsd Card (Max Support 128gb)
	Button	1 Reset Button, 1 Switch Button
Installation	Installation Method	1/4" Universal Screw Hole
Environment	Dustproof And Waterproof	IP65
	Working Environment	-10° ~ 45°c / 10% ~ 80% (No Condensation)
	Storage Environment	-20° C ~ 60° / 0% ~ 90% (No Condensation)
Specification	Size (L x W x H)	67mm x 58mm x 89mm
		4 010
	Weight (Bare Metal)	Approx. 212g
	Weight (Bare Metal) Finished Weight	Approx. 212g Approx. 500g
		- · ·
	Finished Weight	Approx. 500g